

## 2. GRAPHIC BUFFER MEMORY PRODUCT GUIDE

| Density | Orgnization | Power Supply | Part Number | Speed (ns) | Features        | Package  | Remark |
|---------|-------------|--------------|-------------|------------|-----------------|----------|--------|
| 4Mbit   | 256K x 16   | 5V±10%       | KM4216C255  | 60/70/80   | F/F (2WE)       | 64 SSOP  | Now    |
|         |             |              | KM4216C256  | 60/70/80   | F/F (EDO, 2WE)  |          | Now    |
|         |             |              | KM4216C258  | 60/70/80   | F/F (EDO, 2CAS) |          | Now    |
|         |             | 3.3V±10%     | KM4216V255  | 60/70/80   | F/F (2WE)       | 64 SSOP  | Now    |
|         |             |              | KM4216V256  | 60/70/80   | F/F (EDO, 2WE)  |          | Now    |
|         |             |              | KM4216V258  | 60/70/80   | F/F (EDO, 2CAS) |          | Now    |
| 8Mbit   | 256K x 32   | 5V±10%       | KM4232W259  | 60/70      | (EDO, 4BE)      | 120 PQFP | Now    |
|         |             |              | KM4232W259A | 50/60      |                 |          | Now    |
| 8Mbit   | 256K x 32   | 3.3V±0.30V   | KM4132G271  | 10/12/13   | SGRAM, 2Bank    | 100 PQFP | Now    |
|         |             |              | KM4132G271A | 7/8/10/12  |                 |          | 96,12  |